

SPCIFICATION

Specification	Model	AE-A-Pro 22/44KW-W
AC Nominal Input	Phases/Lines	3-Phase+Neutral+PE
	Voltage	400V±10%
	Frequency	50/60Hz
AC Nominal Output	Voltage	400V±10%
	Current	2*16/32A
	Power	2*11KW/2*22KW
Configurations	Charging Outlet	Dual Type 2 Socket/Cable
	Cable Length	Socket/5M
	LED Indicator	Yes
	LCD Screen	4.3" screen for charging data
	RFID Reader	Yes
	RFID Card	Mifare card
	Energy Meter	MID certified meter
	RCD	Type A+6mA DC
	Network Module	WiFi+Bluetooth (LAN,4G for optional)
	Communication Protocol	OCPP 1.6 Json
Environmental Index	Installation Method	Wall-mounted
	Operation Temperature	-30~+50°C
	Working Humidity	5-95% without condensation
	Working Altitude	2000M
	Protection Grade	IP54
	Application Site	Indoor/Outdoor
	Cooling Method	Natural cooling
Security Protection	Multiple Protection	Over/Under voltage protection, Overload protection, Short circuit protection,Current leakage protection, Grounding protection, Surge protection, Over/Under temperature protection
	Safety Standard	IEC 61851-1, IEC 62196-2
	Warranty	2 years
Package Information	Product Dimension	384*323*185mm
	Package Dimension	550*390*370mm
	Net Weight	14KG
	Gross Weight	15KG

AC Dual Outlet Charging Point 2*11kW/2*22kW Wallbox

Features

- Fast charging 11kW/22kW
- WiFi&Bluetooth4G/Ethernet
- Easy installation&maintenance
- DLB &Solar charging
- Full chain encryption
- TypeA+DC6mA (TUV RCD+RCCB)
- IP55,IK10
- Multiple security protections
- Long-term use of 100,000 times
- Mobile APP control,RFID,plug&play
- OCPP,OTA Smart scheduled charging

