

22kW/11kW/7kW Smart Commercial AC Charger

Features

- CE certification
- Fast charging 22kW/11kW/7kW
- WiFi&Bluetooth 4G/Ethernet
- Easy installation&maintenance
- DLB &Solar charging
- Full chain encryption
- TypeA+DC6mA (TUV RCD+RCCB)
- IP55,IK10
- Multiple security protections
- Long-term use of 100,000 times
- Mobile APP control,RFID,plug&play
- OCPP,OTA Smart scheduled charging



SPECIFICATION

| | | |
|---------------------|------------------------|---|
| Specification | Model | AE-A-G-Pro 7/11/22KW |
| AC NominalInput | Phases/Lines | 1/3-Phase+Neutral+PE |
| | Voltage | 230V±10%/400V±10% |
| | Frequency | 50/60Hz |
| AC NominalOutput | Voltage | 230V±10%/400V±10% |
| | Current | 16/32A |
| | Power | 7/11/22KW |
| Configurations | Charging Outlet | Type 2 |
| | Cable Length | 5M |
| | LED Indicator | Yes |
| | LCD Screen | 3.8" screen for charging data |
| | Touch Buttons | Yes |
| | RFID Reader | Yes |
| | RFID Card | 2pcs Mifare card |
| | Energy Meter | MID certified meter for optional |
| | RCD | Type A+6mA DC |
| | Network Module | WiFi+Bluetooth (LAN,4G for optional) |
| | Communication Protocol | OCPP 1.6 Json |
| | App | Yes |
| Environmental Index | Installation Method | Wall-mounted |
| | Operation Temperature | -30~+50°C |
| | Working Humidity | 5-95% without condensation |
| | Working Altitude | 2000M |
| | Protection Grade | IP55 |
| | Application Site | Indoor/Outdoor |
| | Cooling Method | Natural cooling |
| Security Protection | Multiple Protection | Over/Under voltage protection, Overload protection, Short circuit protection,Current leakageprotection, Grounding protection, Surge protection, Over/Under temperature protection |
| | Safety Standard | IEC 61851-1, IEC 62196-2 |
| | Warranty | 2 years |
| Package Information | Product Dimension | 390*205*115mm |
| | Package Dimension | 445*260*230mm |
| | Net Weight | 4KG |
| | Gross Weight | 5KG |